

# VDH010-A

## Manually Actuated Coarse Gas Dosing Valve

### ADVANTAGES

- For admitting a reproducible flow of gas into a vacuum chamber



### SELECTION DATA

Vacuum connection		DN 10 ISO-KF
Gas flow, controllable		
Min.	mbar l/s	40
Max.	mbar l/s	1700

### ORDERING INFORMATION

Type	<b>VDH010-A</b>
Part No.	<b>250-520</b>


### SPECIFICATIONS

Tightness	mbar l/s	$1 \times 10^{-8}$
Pressure range	mbar to bar	$1 \times 10^{-7}$ to 4
Bakeout temperature	°C	100
Housing		aluminum
Seals		FPM
Weight	kg	0.2

### SPARE PARTS

Seal set	<b>215-207</b>
----------	----------------

### DIMENSIONS





**GLOBAL HEADQUARTERS:**

---

Two Technology Place, East Syracuse, NY 13057 USA  
Tel: +1.315.434.1100 Fax: +1.315.437.3803 E-mail: reachus@inficon.com

**UNITED STATES FRANCE GERMANY LIECHTENSTEIN SWITZERLAND UNITED KINGDOM CHINA JAPAN KOREA SINGAPORE TAIWAN**

Visit our website for contact information and other sales offices worldwide. [www.inficon.com](http://www.inficon.com)  
Due to our continuing program of product improvements, specifications are subject to change without notice.  
siba25e1 (2004-05) ©2003 INFICON Inc.