

리테이닝 링이 있는 칼라 플랜지

INFICON ISO-F 고품질 피팅은 ISO 1609, DIN 28404 및 Pneurop 6606에 따라 제작됩니다. 당사의 고품질 대구경 피팅은 모든 진공 및 고진공 제품군의 표준 진공 구성품입니다. 고품질 INFICON 피팅은 1 x 10-9mbar l/s 미만의 누출률용으로 설계되고 테스트되었습니다.



장점

- 경쟁력 있는 가격 책정
- 세계적인 물류
- 설계 및 축정은 국제적인 표준을 엄격히 따릅니다.
- 표면 마감, 용접, 재료 사양 및 청결성은 높은 진공 사양을 충족하거나 초과합니다.
- 2011/65/EU RoHS 준수

주문 정보

유형	DN 63 ISO-F	DN 80 ISO-F	DN 100 ISO-F	DN 160 ISO-F	DN 200 ISO-F	DN 250 ISO-F
Collar flange with retaining ring DN 100			212-062			
Collar flange with retaining ring DN 160				212-063		
Collar flange with retaining ring DN 200					212-064	
Collar flange with retaining ring DN 250						212-065
Collar flange with retaining ring DN 320						
Collar flange with retaining ring DN 400						
Collar flange with retaining ring DN 500						
Collar flange with retaining ring DN 63	212-061					
Collar flange with retaining ring DN 630						
Collar flange with retaining ring DN 80			212-081			

사양

유형	DN 63 ISO-F	DN 80 ISO-F	DN 100 ISO-F	DN 160 ISO-F	DN 200 ISO-F	DN 250 ISO-F
치수 A	12	12	12	16	16	16
치수 B	95.5	110.5	130.5	180.7	240.7	290.7
치수 C	130	145	165	225	285	335
재료:	Steel nickel plated -/1.0831	Steel nickel plated -/1.0831	Steel nickel plated -/1.0831	Steel nickel plated -/1.0831	Steel nickel plated -/1.0037	Steel nickel plated -/1.0037

DN 320 ISO- DN 400 ISO- DN 500 ISO- DN 630 ISO-
 F F F F

212-066


212-067

212-068

212-069

사양

유형	DN 320 ISO-	DN 400 ISO-	DN 500 ISO-	DN 630 ISO-
	F	F	F	F
치수 A	20	20	20	24
치수 B	370.8	450.8	550.8	691
치수 C	425	510	610	750
재료:	Steel nickel plated -/1.0037	Steel nickel plated -/1.0037	Steel nickel plated -/1.0037	Steel nickel plated -/1.0037



www.inficon.com reachus@inficon.com

지속적인 제품 개선 프로그램을 위해 사전 고지 없이 사양이 변경될 수 있습니다.
RateWatcher는 INFICON의 등록상표입니다. 본 사이트에 있는 다른 모든 상표들은 각 소유자의 재산입니다.

(2021-07) © 2021 INFICON