

Multipoint Refrigerant Monitors

Simple monitoring for up to 6 channels.

INFICON multipoint monitors are simple, reliable and safe solutions for standalone constant monitoring of most refrigerant gas. These monitors are a true “plug and play” option! See how these monitors fit any application.



ADVANTAGES

- Multipoint monitor available with up to six channels
- Low maintenance, single point calibration
- Easy field service
- Three adjustable alarm setpoints
- Low voltage operation
- Three relay outputs tie to any system or device
- Designed for any size application
- Factory calibrated
- Detects all CFCs, HFCs, HFOs, HCFCs, or CFCs

MULTIPOINT REFRIGERANT MONITORS (SENSORS INCLUDED)

SPECIFICATIONS			
PART NUMBER	743-250-G1	743-450-G1	743-650-G1
Compatible refrigerants	HFCs, HCFCs, and HFOs		
Power input	12-24 V (AC/DC), 50-60Hz		
Cable length	Not included (user provided)		
Certification	CE, IP54 (sensor), IP67 (monitor),		
Alarm indication	Three alarm levels with relay outputs (5A)		
Sensor type	Surface reaction		
Sensors included	2	4	6

ACCESSORIES/REPLACEMENT PARTS

Blue siren with alarm	743-707-G2
Red siren with alarm	743-707-G1
MCT150 calibration tool	743-600-G1
Replacement sensor module for MCT150 (HFC)	743-706-G1
Replacement sensor for LDMR (HFC)	743-704-G1

