

## Sealing Disk FPM

---

INFICON ISO-F quality fittings are manufactured according to ISO 1609, DIN 28404 and Pneurop 6606. Our quality large diameter fittings are the standard vacuum components for all vacuum and high vacuum lines. The high quality INFICON fittings are designed and tested for leak rates less than  $1 \times 10^{-9}$  mbar l/s.



### BENEFICIOS

---

- Competitively priced
- World wide logistics
- Design and measures follow strictly international respected standards
- 2011/65/EU RoHS compliant

### INFORMACIÓN DEL PEDIDO

---

Tipo	DN100 ISO-F	DN160 ISO-F	DN200 ISO-F	DN250 ISO-F
Vacuum sealing, Al, FPM, DN 100 ISO-F	212-482			
Vacuum sealing, Al, FPM, DN 160 ISO-F		212-483		
Vacuum sealing, Al, FPM, DN 200 ISO-F			212-484	
Vacuum sealing, Al, FPM, DN 250 ISO-F				212-485

## ESPECIFICACIONES

Tipo		DN100 ISO-F	DN160 ISO-F	DN200 ISO-F	DN250 ISO-F
Dimension A:	mm	107	160	220	270
Dimension B:	mm	3.9	3.9	3.9	3.9
Dimension C:	mm	132	185	245	295
Disk:		Aluminum 6082	Aluminum 6082	Aluminum 6082	Aluminum 6082
Seal:		FPM	FPM	FPM	FPM

## DIMENSIONES



[www.inficon.com](http://www.inficon.com)    [reachus@inficon.com](mailto:reachus@inficon.com)

Debido a nuestro programa continuo de mejoras en los productos, las especificaciones están sujetas a modificaciones sin previo aviso. RateWatcher es una marca comercial de INFICON. El resto de marcas comerciales son propiedad de sus respectivos propietarios.

(2018-08)    © 2018 INFICON