

HLD5000 Refrigerant Leak Detector

IR Technology

We've Cut False Alarms, and the Cost of Ownership

The HLD5000 is for use in the production of air conditioning systems, to assure product quality and minimize warranty costs. The HLD5000 Refrigerant Leak Detector uses an innovative technology to find leaks quickly and reliably with dramatically fewer false alarms. Its newly developed IR sensor offers a substantially extended sensor life. With its dual gas inlet (patent pending) it reliably suppresses any signals caused by other gases present in the atmosphere. The instrument reduces the cost of ownership not only by the extended sensor life, but also by improving the lifetime of all mechanical and electronic parts, and minimizing the number of consumables and their cost.



A selection of probes for different gases is available. The HLD5000 can also be used with the new Smart probe.

ES-ES:FEATURES

- Fast and easy to use
- Lower cost of ownership
- Superior stability
- Durable for longer life
- Easy programming
- Versions for many refrigerants
- Automatic standby function
- Built-in calibrated leak
- Easy to move and install

es-es:Type	HLD5000
	510-010

ES-ES:SPECIFICATIONS

es-es:Type	HLD5000
Singel gas probe	R134a; R744 (CO ₂), R600a/R290
Universal Smart probe	all halogen-based refrigerants
Single gas probe	0 - 100 g/a (3.57 oz/yr)
Response time	< 1 s
Leak rate units	g/a; mbar l/s; oz/yr; lb/yr; Pa m ³ /s, ppm
Warm-up time	30 s
Dimensions (diameter; height)	260 mm (10.25 in.); 365 mm (14.4 in.)
Weight	4.5 kg (10 lbs)
Length of sniffer line	4.8 m (15.5 ft.)
Standard sniffer tip length	100 mm (3.9 in.)
Gas flow	320 sccm
Ambient temperature range	5 - 50°C (40 - 120°F)

ES-ES:ACCESSORIES

HLD5000

ES-ES:CONSUMABLES

HLD5000



www.inficon.com reachus@inficon.com

es-es:Due to our continuing program of product improvements, specifications are subject to change without notice.
es-es:RateWatcher is a trademark of INFICON. All other trademarks are the property of their respective owners.

(2013-03) © 2012 INFICON